Silver Scan-Tool Version 6.24.36.29970 Copyright by RA Consulting GmbH Registered for Daniel Ogden

Date: 01/16/2020, 06:04:39 pm

Measurement file: C:\RA Consulting\Silver Scan-Tool\user\SEMA_2015_EcoBoost_M.dra

Interface: VSI-2534
Driver Version: 2.8.0.0

Vehicle

Derive 2011 Ford F-250 SEMA Garage _ Rene Acosta _ Derive 2011 Ford F250_ Mileage 78823_ OBD Report (Post FTP 2)

Acquisition worker:

Location: Department:

ECU

33 Scan-Tool

Protocol: ISO 15765-4 (CAN)

List of supported Modes and PIDs

Mode	PID	Module	Comment	
Mode 1	****	****	Current powertrain diagnostic data	
1	00	E8 E9	PIDs supported 01-1F	
1	01	E8 E9	Monitor status since DTCs cleared	
1	04	E8 E9	Calculated load value	
1	05	E9	Engine coolant temperature	
1	0C	E8 E9	Engine RPM	
1	0D	E8 E9	Vehicle speed sensor	
1	0F	E9	Intake air temperature	
1	13	E8	Location of oxygen sensors	
1	1 C	E8 E9	OBD requirements to which vehicle or engine is certified	
1	1 F	E8 E9	Time since engine start	
1	20	E8 E9	PIDs supported 21-3F	
1	21	E8 E9	Distance traveled while MIL is activated	
1	24	E8	Equivalence ratio, Oxygen sensor voltage	
1	2F	E8	Fuel level input	
1	30	E8 E9	Number of warm-ups since DTCs cleared	
1	31	E8 E9	Distance traveled since DTCs cleared	
1	33	E8 E9	Barometric pressure	
1	40	E8 E9	PIDs supported 41-5F	
1	41	E8	Monitor status this driving cycle	
1	42	E8 E9	Control module voltage	
1	46	E8	Ambient air temperature	
1	49	E8 E9	Accelerator pedal position D	
1	4A	E8	Accelerator pedal position E	
1	4F	E8	External Test Equipment Configuration Information #1	

```
1
            51
                        E8
                                    Type of fuel currently being utilized by the internal combustion
engine
            5C
                        E8
                                    Engine oil temperature
1
                                    Fuel injection timing
            5D
                        E8
1
1
            5E
                        E8
                                    Engine fuel rate
1
            60
                        F٨
                                    PIDs supported 61-7F
                                    Driver's demand engine - percent torque
1
            61
                        F۸
                        E8
                                    Actual engine - percent torque
1
            62
                        E8
                                    Engine reference torque
1
            63
                                    Engine percent torque at idle point 1, Engine percent torque at
            64
                        E8
point 2, Engine percent torque at point 3, Engine percent torque at point 4, Engine percent torque at
point 5
                                    Auxiliary Inputs/Outputs Status
            65
                        E8
1
                        E8
                                    Mass Air Flow Sensor A, Mass Air Flow Sensor B
1
            66
            67
                        E8
                                    Engine Coolant Temperature 1, Engine Coolant Temperature 2
1
            68
                        F8
                                    Intake Air Temperature Bank 1 Sensor 1, Intake Air Temperature
Bank 1 Sensor 2, Intake Air Temperature Bank 1 Sensor 3, Intake Air Temperature Bank 2 Sensor 1,
Intake Air Temperature Bank 2 Sensor 2, Intake Air Temperature Bank 2 Sensor 3
                                    Commanded EGR A Duty Cycle/Position, Actual EGR A Duty
                        E8
Cycle/Position, EGR A Error, Commanded EGR B Duty Cycle/Position, Actual EGR B Duty Cycle/Position,
EGR B Error
            6A
                        E8
                                    Commanded Intake Air Flow A Control, Relative Intake Air Flow A
1
Position, Commanded Intake Air Flow B Control, Relative Intake Air Flow B Position
                                    Exhaust Gas Recirculation Temp Sensor A (Bank 1 Sensor 1), Exhaust
                        E8
Gas Recirculation Temp Sensor C (Bank 1 Sensor 2), Exhaust Gas Recirculation Temp Sensor B (Bank 2
Sensor 1), Exhaust Gas Recirculation Temp Sensor D (Bank 2 Sensor 2)
                        E8
                                    Commanded Fuel Rail Pressure A, Fuel Rail Pressure A, Fuel Rail
Temperature A, Commanded Fuel Rail Pressure B, Fuel Rail Pressure B, Fuel Rail Temperature B
                                    Commanded Variable Geometry Turbo A Position, Variable Geometry
            71
                        E8
Turbo A Position, VGT A Control Status, Commanded Variable Geometry Turbo B Position, Variable
Geometry Turbo B Position, VGT A,B Control Status
                                    Commanded Wastegate A Position, Wastegate A Position, Commanded
            72
                        E8
Wastegate B Position, Wastegate B Position
                                    Exhaust Pressure Sensor Bank 1, Exhaust Pressure Sensor Bank 2
1
            73
                        E8
                                    Charge Air Cooler Temperature Bank 1 Sensor 1, Charge Air Cooler
            77
                        E8
Temperature Bank 1 Sensor 2, Charge Air Cooler Temperature Bank 2 Sensor 1, Charge Air Cooler
Temperature Bank 2 Sensor 2
            78
                        F8
                                    Exhaust Gas Temperature Bank 1 Sensor 1, Exhaust Gas Temperature
1
Bank 1 Sensor 2, Exhaust Gas Temperature Bank 1 Sensor 3, Exhaust Gas Temperature Bank 1 Sensor 4
                                    Diesel Particulate Filter Bank 1 Delta Pressure, Diesel
                        E8
Particulate Filter Bank 1 Inlet Pressure, Diesel Particulate Filter Bank 1 Outlet Pressure
            7D
                                    NOx NTE control area status
1
                        E8
            7E
                        E8
                                    PM NTE control area status
1
                                    Total Engine Run Time, Total Idle Run Time, Total Run Time With
            7F
                        E8
PTO Active
            80
                        E8
                                    PIDs supported 81-9F
1
                                    Total run time with EI-AECD #1 Timer 1 active, Total run time with
                        E8
EI-AECD #1 Timer 2 active, Total run time with EI-AECD #2 Timer 1 active, Total run time with EI-AECD
#2 Timer 2 active, Total run time with EI-AECD #3 Timer 1 active, Total run time with EI-AECD #3 Timer
2 active, Total run time with EI-AECD #4 Timer 1 active, Total run time with EI-AECD #4 Timer 2
active, Total run time with EI-AECD #5 Timer 1 active, Total run time with EI-AECD #5 Timer 2 active
                                    Total run time with EI-AECD #6 Timer 1 active, Total run time with
            82
                        E8
EI-AECD #6 Timer 2 active, Total run time with EI-AECD #7 Timer 1 active, Total run time with EI-AECD
#7 Timer 2 active, Total run time with EI-AECD #8 Timer 1 active, Total run time with EI-AECD #8 Timer
2 active, Total run time with EI-AECD #9 Timer 1 active, Total run time with EI-AECD #9 Timer 2
active, Total run time with EI-AECD #10 Timer 1 active, Total run time with EI-AECD #10 Timer 2 active
                                    NOx Sensor Concentration Bank 1 Sensor 1, NOx Sensor Concentration
                        E8
Bank 1 Sensor 2, NOx Sensor Concentration Bank 2 Sensor 1, NOx Sensor Concentration Bank 2 Sensor 2
                                    Average Reagent Consumption, Average Demanded Reagent Consumption,
                        E8
Reagent Tank Level, Total run time by the engine while NOx warning mode is activated
                                    Intake Manifold Absolute Pressure A, Intake Manifold Absolute
            87
                        E8
```

```
Pressure B
```

```
1 89 E8 Total run time with EI-AECD #11 Timer 1 active, Total run time with EI-AECD #12 Timer 2 active, Total run time with EI-AECD #12 Timer 1 active, Total run time with EI-AECD #13 Timer 2 active, Total run time with EI-AECD #13 Timer 1 active, Total run time with EI-AECD #14 Timer 1 active, Total run time with EI-AECD #14 Timer 2 active, Total run time with EI-AECD #15 Timer 2 active
1 8A E8 Total run time with EI-AECD #16 Timer 1 active, Total run time with EI-AECD #17 Timer 2 active, Total run time with EI-AECD #17 Timer 2 active, Total run time with EI-AECD #18 Timer 2 active, Total run time with EI-AECD #18 Timer 1 active, Total run time with EI-AECD #18 Timer 2 active, Total run time with EI-AECD #19 Timer 2 active, Total run time with EI-AECD #19 Timer 2 active, Total run time with EI-AECD #19 Timer 2 active, Total run time with EI-AECD #20 Timer 2 active, Total run time with EI-AECD #20 Timer 2 active
```

1 8B E8 Diesel Aftertreatment Status, Normalized Trigger for DPF Regen, Average Time Between DPF Regens, Average Distance Between DPF Regens

· ·		0 ,			
Mode 2	Frame 0	****	Current freeze frame data		
2	00	E8 E9	PIDs supported 01-1F		
2	01	E9	Monitor status since DTCs cleared		
2	02	E8 E9	DTC that caused required freeze frame data storage		
2	04	E8 E9	Calculated load value		
2	05	E9	Engine coolant temperature		
2	0C	E8 E9	Engine RPM		
2	0D	E8 E9	Vehicle speed sensor		
2	0F	E9	Intake air temperature		
2	1F	E8 E9	Time since engine start		
2	20	E8 E9	PIDs supported 21-3F		
2	2F	E8	Fuel level input		
2	30	E9	Number of warm-ups since DTCs cleared		
2	31	E9	Distance traveled since DTCs cleared		
2	33	E8 E9	Barometric pressure		
2	40	E8 E9	PIDs supported 41-5F		
2	42	E8 E9	Control module voltage		
2	46	E8	Ambient air temperature		
2	49	E8 E9	Accelerator pedal position D		
2	4A	E8	Accelerator pedal position E		
2	5C	E8	Engine oil temperature		
2	5D	E8	Fuel injection timing		
2	5E	E8	Engine fuel rate		
2	60	E8	PIDs supported 61-7F		
2	61	E8	Driver's demand engine - percent torque		
2	62	E8	Actual engine - percent torque		
2	63	E8	Engine reference torque		
2	64	E8	Engine percent torque at idle point 1, Engine percent torque at		
point 2, En	gine percent	torque at p	point 3, Engine percent torque at point 4, Engine percent torque at		
point 5					
2	65	E8	Auxiliary Inputs/Outputs Status		
2	66	E8	Mass Air Flow Sensor A, Mass Air Flow Sensor B		
2	67	E8	Engine Coolant Temperature 1, Engine Coolant Temperature 2		
2	68	E8	Intake Air Temperature Bank 1 Sensor 1, Intake Air Temperature		
Bank 1 Sens	or 2, Intake	Air Tempera	ature Bank 1 Sensor 3, Intake Air Temperature Bank 2 Sensor 1,		
Intake Air	Temperature	Bank 2 Senso	or 2, Intake Air Temperature Bank 2 Sensor 3		
2	69	E8	Commanded EGR A Duty Cycle/Position, Actual EGR A Duty		
Cycle/Position, EGR A Error, Commanded EGR B Duty Cycle/Position, Actual EGR B Duty Cycle/Position, EGR B Error					
2	6A	E8	Commanded Intake Air Flow A Control, Relative Intake Air Flow A		
Position, C	ommanded Int	ake Air Flow	N B Control, Relative Intake Air Flow B Position		
2	6B	E8	Exhaust Gas Recirculation Temp Sensor A (Bank 1 Sensor 1), Exhaust		
Gas Recirculation Temp Sensor C (Bank 1 Sensor 2), Exhaust Gas Recirculation Temp Sensor B (Bank 2					
Sensor 1), Exhaust Gas Recirculation Temp Sensor D (Bank 2 Sensor 2)					
2	6D	E8	Commanded Fuel Rail Pressure A, Fuel Rail Pressure A, Fuel Rail		

```
Temperature A, Commanded Fuel Rail Pressure B, Fuel Rail Pressure B, Fuel Rail Temperature B
            71
                                     Commanded Variable Geometry Turbo A Position, Variable Geometry
                        E8
Turbo A Position, VGT A Control Status, Commanded Variable Geometry Turbo B Position, Variable
Geometry Turbo B Position, VGT A,B Control Status
                        E8
                                     Commanded Wastegate A Position, Wastegate A Position, Commanded
Wastegate B Position, Wastegate B Position
                                     Exhaust Pressure Sensor Bank 1, Exhaust Pressure Sensor Bank 2
2
            73
                        E8
            77
                                     Charge Air Cooler Temperature Bank 1 Sensor 1, Charge Air Cooler
                        E8
Temperature Bank 1 Sensor 2, Charge Air Cooler Temperature Bank 2 Sensor 1, Charge Air Cooler
Temperature Bank 2 Sensor 2
                                     Exhaust Gas Temperature Bank 1 Sensor 1, Exhaust Gas Temperature
            78
Bank 1 Sensor 2, Exhaust Gas Temperature Bank 1 Sensor 3, Exhaust Gas Temperature Bank 1 Sensor 4
                                     Diesel Particulate Filter Bank 1 Delta Pressure, Diesel
2
            7Α
                        E8
Particulate Filter Bank 1 Inlet Pressure, Diesel Particulate Filter Bank 1 Outlet Pressure
                                     Total Engine Run Time, Total Idle Run Time, Total Run Time With
            7F
                        F8
PTO Active
2
            80
                        E8
                                     PIDs supported 81-9F
            85
                        E8
                                     Average Reagent Consumption, Average Demanded Reagent Consumption,
Reagent Tank Level, Total run time by the engine while NOx warning mode is activated
                                     Intake Manifold Absolute Pressure A, Intake Manifold Absolute
2
                        E8
Pressure B
                        E8
                                     Diesel Aftertreatment Status, Normalized Trigger for DPF Regen,
Average Time Between DPF Regens, Average Distance Between DPF Regens
Mode 3
                                     Emission-related diagnostic trouble codes
Mode 4
                                     Clear/reset emission-related diagnostic information
            ****
                        ****
Mode 6
                                     Monitoring test results for specific monitored systems
            99
                        F٨
                                     MIDs supported 01-1F
6
                                     Exhaust Gas Sensor Monitor Bank 1 - Sensor 1
            91
                        E8
6
                                     MIDs supported 21-3F
6
            20
                        F۸
6
            21
                        E8
                                     Catalyst Monitor Bank 1
            34
                        E8
                                     EGR Monitor Bank 4
6
            40
                                     MIDs supported 41-5F
6
                        F8
                                     MIDs supported 61-7F
6
            60
                        F8
                                     MIDs supported 81-9F
6
            80
                        F8
6
            81
                        F8
                                     Fuel System Monitor Bank 1
            82
                        E8
                                     Fuel System Monitor Bank 2
6
6
            85
                        E8
                                     Boost Pressure Control Monitor Bank 1
6
            98
                        E8
                                     NOx/SCR Catalyst Monitor Bank 1
                                     MIDs supported A1-BF
6
            ΔΘ
                        E8
6
            Δ2
                        E8
                                     Misfire Cylinder 1 Data
6
            Δ3
                        E8
                                     Misfire Cylinder 2 Data
                                     Misfire Cylinder 3 Data
6
            Α4
                        E8
            Α5
                                     Misfire Cylinder 4 Data
6
                        E8
                                     Misfire Cylinder 5 Data
6
            A6
                        E8
                                     Misfire Cylinder 6 Data
6
            Α7
                        F8
6
            Α8
                        F8
                                     Misfire Cylinder 7 Data
6
            Δ9
                        F8
                                     Misfire Cylinder 8 Data
                                     PM Filter Monitor Bank 1
6
            B2
                        F8
Mode 7
            ****
                        ****
                                     Emission-related diagnostic trouble codes detected during current
or last completed driving cycle
            ****
                        ****
Mode 9
                                     Vehicle information
            00
                        E8 E9
                                     Supported INFOTYPEs 01-1F
9
9
                                     Vehicle Identification Number(VIN)
            02
                        E8
9
            04
                        E8 E9
                                     Calibration Identification (CALID)
                                     Calibration Verification Numbers (CVN)
9
            96
                        E8 E9
9
                                     ECU Name
            9A
                        F8 F9
```

Scan-Tool Mode 1 - Current powertrain diagnostic data

PID 61

PID 62

PID 63

%

%

Nm

0

0

999

E8 ECM-EngineControl PID 01 0000 0000 MIL off, 0 fault code entries 0000 1111 1110 1011 0000 0000 Monitor status since DTCs cleared Misfire monitoring supported and complete Fuel system monitoring supported and complete Comprehensive component monitoring supported and complete NMHC catalyst monitoring supported and complete NOx/SCR aftertreatment monitoring supported and complete Boost pressure system monitoring supported and complete Exhaust gas sensor monitoring supported and complete PM filter monitoring supported and complete EGR and/or VVT system monitoring supported and complete PID 04 Calculated load value 0.0 % PID 0C 1/min Engine RPM 0 PID 0D 0 km/h Vehicle speed sensor PID 13 0000 0001 Location of oxygen sensors Bank 1 Sensor 1 OBD requirements to which vehicle or engine is certified (OBD and OBD II) PID 1C 3 PID 1F 0 Time since engine start s PID 21 0 Distance traveled while MIL is activated km 1.000 PID 24 Lambda Equivalence ratio Bank 1 Sensor 1 Oxygen sensor voltage Bank 1 Sensor 1 0.000 V PID 2F 22.0 % Fuel level input PID 30 Number of warm-ups since DTCs cleared 35 dec PID 31 Distance traveled since DTCs cleared 1053 km PID 33 Barometric pressure 99 kPa PID 41 0000 0000 0111 1000 1110 0000 1110 0011 Monitor status this driving cycle Misfire monitoring disabled Fuel system monitoring disabled Comprehensive component monitoring disabled NMHC catalyst monitoring disabled NOx/SCR aftertreatment monitoring disabled Boost pressure system monitoring disabled and complete Exhaust gas sensor monitoring enabled PM filter monitoring enabled EGR and/or VVT system monitoring enabled PID 42 12.260 V Control module voltage PID 46 °C Ambient air temperature 24 PID 49 15.3 % Accelerator pedal position D PID 4A 7.5 % Accelerator pedal position E PID 51 4 Type of fuel currently being utilized by the internal combustion engine Diesel PID 5C 74 °C Engine oil temperature PID 5D 0 Fuel injection timing 0.00 PID 5E 0.00 L/h Engine fuel rate

Driver's demand engine - percent torque

Actual engine - percent torque

Engine reference torque

```
PID 64
                        Engine percent torque at idle point 1
           34
           34
                %
                        Engine percent torque at point 2
           34
                %
                        Engine percent torque at point 3
           34
                %
                        Engine percent torque at point 4
           34
                %
                        Engine percent torque at point 5
PID 65
       0000 0000
                        Auxiliary Inputs/Outputs Status
                        Power Take Off not active (OFF)
                        Auto Trans in Park/Neutral
                        Glow Plug Lamp OFF
PID 66
                        Mass Air Flow Sensor A
         0.22
                g/s
PID 67
           81
                °C
                        Engine Coolant Temperature 1
                °C
                        Engine Coolant Temperature 2
           81
PID 68
                °C
                        Intake Air Temperature Bank 1 Sensor 1
           54
PID 69
          4.7
                %
                        Commanded EGR A Duty Cycle/Position
          0.0
                %
                        Actual EGR A Duty Cycle/Position
        -100.0
                %
                        EGR A Error
                        Commanded Intake Air Flow A Control
PID 6A
          0.0
                %
          9.4
                %
                        Relative Intake Air Flow A Position
                        Exhaust Gas Recirculation Temp Sensor A (Bank 1 Sensor 1)
                °C
PID 6B
           75
                °C
                        Exhaust Gas Recirculation Temp Sensor C (Bank 1 Sensor 2)
           81
                        Commanded Fuel Rail Pressure A
PID 6D
        30000
                kPa
         2570
                kPa
                        Fuel Rail Pressure A
          8.2
                        Commanded Variable Geometry Turbo A Position
                %
PID 71
                %
                        Variable Geometry Turbo A Position
          0.0
        0000 0001
                        VGT A,B Control Status
PID 72
         73.7
                        Commanded Wastegate A Position
                %
          0.0
                %
                        Wastegate A Position
PID 73
        98.90
                kPa
                        Exhaust Pressure Sensor Bank 1
                °C
                        Charge Air Cooler Temperature Bank 1 Sensor 1
PID 77
           53
           53
                °C
                        Charge Air Cooler Temperature Bank 1 Sensor 2
PID 78
         51.2
                °C
                        Exhaust Gas Temperature Bank 1 Sensor 1
        102.0
                °C
                        Exhaust Gas Temperature Bank 1 Sensor 2
        135.0
                °C
                        Exhaust Gas Temperature Bank 1 Sensor 3
         93.4
                °C
                        Exhaust Gas Temperature Bank 1 Sensor 4
         0.00
                        Diesel Particulate Filter Bank 1 Inlet Pressure
PTD 7A
                kPa
PID 7D
       0000 0010
                        NOx NTE control area status
                        outside control area
PID 7E 0000 0010
                        PM NTE control area status
                        outside control area
       33 hrs 9 min 15 s
                                 Total Engine Run Time
        9 hrs 1 min 2 s Total Idle Run Time
        0 min 0 s
                        Total Run Time With PTO Active
PID 81
       0 min 0 s
                        Total run time with EI-AECD #1 Timer 1 active
        0 min 2 s
                        Total run time with EI-AECD #1 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #2 Timer 1 active
        47 min 52 s
                        Total run time with EI-AECD #2 Timer 2 active
        7 hrs 30 min 0 s
                                Total run time with EI-AECD #3 Timer 1 active
        1 hrs 44 min 36 s
                                Total run time with EI-AECD #3 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #4 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #4 Timer 2 active
        54 min 6 s
                        Total run time with EI-AECD #5 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #5 Timer 2 active
PID 82 0 min 2 s
                        Total run time with EI-AECD #6 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #6 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #7 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #7 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #8 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #8 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #9 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #9 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #10 Timer 1 active
```

```
0 min 0 s
                        Total run time with EI-AECD #10 Timer 2 active
PID 83
                        NOx Sensor Concentration Bank 1 Sensor 1
                mag
                        NOx Sensor Concentration Bank 1 Sensor 2
            0
                ppm
       0.000
                L/h
PID 85
                        Average Reagent Consumption
        0.000
                L/h
                        Average Demanded Reagent Consumption
        100.0
                %
                        (Value = FF) Reagent Tank Level
                        Total run time by the engine while NOx warning mode is activated
        0 min 0 s
PID 87
       96.59
                        Intake Manifold Absolute Pressure A
                kPa
PID 89 0 min 0 s
                        Total run time with EI-AECD #11 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #11 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #12 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #12 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #13 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #13 Timer 2 active
        0 min 0 s
                        Total run time with EI-AECD #14 Timer 1 active
        0 min 0 s
                        Total run time with EI-AECD #14 Timer 2 active
        0 min 7 s
                        Total run time with EI-AECD #15 Timer 1 active
        0 min 2 s
                        Total run time with EI-AECD #15 Timer 2 active
       0 min 0 s
                        Total run time with EI-AECD #16 Timer 1 active
PID 8A
        1193046 hrs 28 min 15 s Total run time with EI-AECD #16 Timer 2 active
PID 8B
       0000 0010
                        Diesel Aftertreatment Status
                        DPF Regen not in progress
                        Active DPF Regen
          854
                        Average Distance Between DPF Regens
                km
   TCM-TransmisCtrl
       0000 0000
                        MIL off, 0 fault code entries
PTD 01
        0000 0100
        0000 0000
        0000 0000
                        Monitor status since DTCs cleared
                        Misfire monitoring not supported
                        Fuel system monitoring not supported
                        Comprehensive component monitoring supported and complete
                        Catalyst monitoring not supported
                        Heated catalyst monitoring not supported
                        Evaporative system monitoring not supported
                        Secondary air system monitoring not supported
                        Oxygen sensor monitoring not supported
                        Oxygen sensor heater monitoring not supported
                        EGR and/or VVT system monitoring not supported
PID 04
          0.0
                        Calculated load value
                        Engine coolant temperature
PID 05
           82
                °C
PID 0C
                1/min
                        Engine RPM
           0
PID 0D
                km/h
                        Vehicle speed sensor
            0
PID 0F
                °C
                        Intake air temperature
           54
PID 1C
                        OBD requirements to which vehicle or engine is certified (OBD and OBD II)
            3
PID 1F
            0
                        Time since engine start
                S
PID 21
                        Distance traveled while MIL is activated
            0
                km
PID 30
                        Number of warm-ups since DTCs cleared
           32
                dec
PID 31
                        Distance traveled since DTCs cleared
         1058
                km
PID 33
          99
                kPa
                        Barometric pressure
PID 42 11.990 V
                        Control module voltage
PID 49
          0.0
                        Accelerator pedal position D
```

Scan-Tool Mode 2 - Current freeze frame data

No fault code entry

E9 TCM-TransmisCtrl

No fault code entry

Scan-Tool Mode 3 - Emission-related diagnostic trouble codes

E8 ECM-EngineControl

MIL off

0 fault code entries

No fault code entry

E9 TCM-TransmisCtrl

MIL off

0 fault code entries

No fault code entry

Scan-Tool Mode 6 - Monitoring test results for specific monitored systems

E8 ECM-EngineControl

Monitor ID	Test ID	Unit ID	Test value	Min value	Max value	Unit	Comment
01		11	3.1	0.0	6.0	S	Exhaust Gas Sensor
Monitor Bank							
	91	11	1.0	0.0	5.0	S	Exhaust Gas Sensor
Monitor Bank		_					
	92	11	4.1	0.0	11.0	S	Exhaust Gas Sensor
Monitor Bank		_					
01		30	7.170204	0.000000	11.300815	%	Exhaust Gas Sensor
Monitor Bank							
01		30	9.677258	2.258332	16.357648	%	Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
01	95	30	19.568142	14.097790	25.496263	%	Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
01	96	83	1.06	0.90	1.22		Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
01	97	81	9	1	100		Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
01	98	B0	-2.291827	-10.000421	0.000000	%	Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
01	99	B0	0.000000	0.000000	19.997790	%	Exhaust Gas Sensor
Monitor Bank	1 - Sensor	1					
21	90	B0	99.988951	39.995580	99.988951	%	Catalyst Monitor
Bank 1							
34	90	AF	2.94	-327.68	23.91	%	EGR Monitor Bank 4
34	91	AF	2.94	-10.22	327.67	%	EGR Monitor Bank 4

34	92	96	93.1	-3276.8	174.5	°C	EGR Monitor Bank 4
34	93	96	132.3	67.1	3276.7	°C	EGR Monitor Bank 4
81	91	3C	546.4	294.0	664.0	μs	Fuel System
	Bank 1	2.0					
81 Monitor	92 ^ Bank 1	3C	530.4	294.0	664.0	μs	Fuel System
81	93	3C	517.6	294.0	664.0	μs	Fuel System
Monitor	Bank 1					•	,
81	94	3C	534.8	294.0	664.0	μs	Fuel System
Monitor 82	↑ Bank 1 95	3C	523.6	294.0	664.0	μs	Fuel System
	Bank 2	30	323.0	254.0	004.0	μο	ruci system
82	96	3C	506.8	294.0	664.0	μs	Fuel System
Monitor 82	r Bank 2 97	3C	522.0	294.0	664.0		Fuel System
	r Bank 2	30	322.0	294.0	004.0	μs	Fuel System
82	98	3C	524.4	294.0	664.0	μs	Fuel System
	Bank 2	4=	0.10	0.04			
85	90 l Monitor Bank 1	17	2.18	2.01	655.35	kPa	Boost Pressure
85	92	FC	-5.70	-15.00	327.67	kPa	Boost Pressure
Control	l Monitor Bank 1						
85	93	AF	-5.93	-327.68	17.20	%	Boost Pressure
Control 85	l Monitor Bank 1 94	17	2.17	2.00	655.35	kPa	Boost Pressure
	l Monitor Bank 1	1,	2.17	2.00	033.33	Ki u	boose i ressare
85	96	96	16.1	-5.0	3003.6	°C	Boost Pressure
	l Monitor Bank 1	DO.	06 735030	24 006806	00 005054	0/	NOV/CCD Catalyst
98 Monitor	90 ~ Bank 1	В0	96.735838	34.996896	99.995054	%	NOx/SCR Catalyst
A2	0B	24	0	0	65535	counts	Misfire Cylinder 1
Data							
A2 Data	0C	24	0	0	65535	counts	Misfire Cylinder 1
A3	0B	24	0	0	65535	counts	Misfire Cylinder 2
Data							•
A3	0C	24	0	0	65535	counts	Misfire Cylinder 2
Data A4	0B	24	0	0	65535	counts	Misfire Cylinder 3
Data		_,	-	-			-
A4	0C	24	0	0	65535	counts	Misfire Cylinder 3
Data A5	0B	24	0	0	65535	counts	Misfire Cylinder 4
Data	OD.	24	O	O	05555	Courtes	MISTITE CYTINGET 4
A 5	0C	24	0	0	65535	counts	Misfire Cylinder 4
Data	0.0	2.4	0	0	CEESE		Mistina Culindan F
A6 Data	0C	24	0	0	65535	counts	Misfire Cylinder 5
A6	0B	24	0	0	65535	counts	Misfire Cylinder 5
Data			_	_			
A7 Data	0C	24	0	0	65535	counts	Misfire Cylinder 6
A7	0C	24	0	0	65535	counts	Misfire Cylinder 6
Data							
A8	0B	24	0	0	65535	counts	Misfire Cylinder 7
Data A8	ØC	24	0	0	65535	counts	Misfire Cylinder 7
Data	00	<u> </u>	5	5		Councs	1123111 C CYTTHUE! /
A9	0B	24	0	0	65535	counts	Misfire Cylinder 8
Data	0.0	2.4	0	0	CEE35	court-	Micfine Culturation C
Α9	0C	24	0	0	65535	counts	Misfire Cylinder 8

Data B2 90 20 46.3203125 10.0000000 100.0000000 PM Filter Monitor Bank 1 E9 TCM-TransmisCtrl Monitor ID Test ID Unit ID Test value Min value Max value Unit Comment Scan-Tool Mode 7 - Emission-related diagnostic trouble codes detected during current or last completed driving cycle ------E8 ECM-EngineControl No fault code entry E9 TCM-TransmisCtrl No fault code entry Scan-Tool Mode 9 - Vehicle information E8 ECM-EngineControl INFOTYPE 02 Vehicle Identification Number(VIN) 1FT7W2BT9BEA15523 INFOTYPE 04 Calibration Identification (CALID) BC3A-14D609-CA BC3A-14F553-BC DDBZ2A6.H32 Calibration Verification Numbers (CVN) INFOTYPE 06 E4 78 EA 0A D8 74 56 60 00 00 76 F8 INFOTYPE 0A ECU Name ECM-EngineControl

INFOTYPE 0B In-use Performance Tracking OBDCOND 49

NADSCOND

General Denominator, OBD Monitoring Conditions Encountered Counts

IGNCNTR 137 Ignition Cycle Counter

0

HCCATCOMP 3 Numerator, NMHC Catalyst Monitor Completion Condition Counts **HCCATCOND** Denominator, NMHC Catalyst Monitor Conditions Encountered Counts 1 3.000 - Calculated Ratio -NCATCOMP 10 Numerator, NOx Catalyst Monitor Completion Condition Counts NCATCOND 49 Denominator, NOx Catalyst Monitor Conditions Encountered Counts 0.204 - Calculated Ratio -NADSCOMP 0 Numerator, NOx Adsorber Monitor Completion Condition Counts

Denominator, NOx Adsorber Monitor Conditions Encountered Counts

7.995 - Calculated Ratio -

PMCOMP 44 PMCOND 1	Numerator, PM Filter Monitor Completion Condition Counts Denominator, PM Filter Monitor Conditions Encountered Counts 7.995 - Calculated Ratio -
EGSCOMP 13 EGSCOND 49	Numerator, Exhaust Gas Sensor Monitor Completion Condition Counts Denominator, Exhaust Gas Sensor Monitor Conditions Encountered Counts 0.265 - Calculated Ratio -
EGRCOMP 61 EGRCOND 49	Numerator, EGR/VVT Monitor Completion Condition Counts Denominator, EGR/VVT Monitor Conditions Encountered Counts 1.245 - Calculated Ratio -
BPCOMP 72 BPCOND 49	Numerator, Boost Pressure Monitor Completion Condition Counts Denominator, Boost Pressure Monitor Conditions Encountered Counts 1.469 - Calculated Ratio -
FUELCOMP FUELCOND	Numerator, Fuel Monitor Completion Condition Counts Denominator, Fuel Monitor Conditions Encountered Counts Calculated Ratio -

E9 TCM-TransmisCtrl

INFOTYPE 04	Calibration	Identification	(CALID)
	TVDDQED H33		

TVDD0FD.H32

INFOTYPE 06 Calibration Verification Numbers (CVN)

8D 12 F7 36

INFOTYPE 0A ECU Name

TCM-TransmisCtrl

Scan-Tool Mode A - Emission-related diagnostic trouble codes with permanent status

E8 ECM-EngineControl

No fault code entry

E9 TCM-TransmisCtrl

No fault code entry